

# SILICONE SOLUTIONS

338 Remington Rd  
Cuyahoga Falls, OH 44224

Phone (330) 920-3125

Fax (330) 920-3126

## SS-301

### Product Description

SS-301 is a fast curing silicone RTV adhesive rubber developed for applications requiring fast development of physical properties and fast unprimed adhesion. SS-301 is a 1-Part silicone that when applied to the substrate allows handling of the bonded assembly within an hour. When cured, the elastomer resists weathering, ozone, moisture, UV and high temperatures. SS-301 works well in manual and automatic dispensing equipment.

### Product Features

- Fast R.T. cure
- Thixotropic paste
- Excellent unprimed adhesion to many composites, metals and glass
- Rapid onset of adhesion
- High temperature resistant
- Non-corrosive oxime cure
- Temperature range -45 to 260C

### Typical Applications

- Industrial bonding
- Form in place gaskets
- Adhesive Sealant

**Colors:** Black and Gray  
(Custom colors available upon request)



## Fast Cure Silicone RTV Adhesive Sealant

### Typical Properties

#### UNCURED

Viscosity, cps	400,000
Specific Gravity	1.29
Consistency :	thixotropic paste
Working time, mins. @ R.T.:	5
Tack Free Time, mins. @ R.T.:	15
Application Rate, 90 PSI, g/min. 3mm orifice @ 0.6 MPa	>1000

#### CURED - R.T.

Cured -72 Hrs. @ R.T.	
Tensile Strength, PSI <sub>275</sub>	
Elongation, %	350
Durometer, Shore A	35
Peel Strength, PPI	30

### Method of Application

Dispense sealant onto part and mate parts. Be sure not to squeeze all of the product out of flange assembly. Allow to cure.

## **Curing**

Cure speed can be accelerated with increased humidity to very rapid cures exhibiting surprisingly fast adhesion. Typical utilization involves dispensing in open air and ambient humidity to result in a high strength adhesive rubber.

## **Chemical cure system**

Oxime cure system

## **Packaging**

SS-301 is available in 10.3 oz. cartridges, 50 lb. pails and 500 lb. drums. This product is also available in customer defined packaging sizes, upon request.

## **Solids**

98% solids, contains no solvents

## **Service Temperature**

-45 -260C

## **Adhesion**

Primerless adhesion to most metals and typical substrates.

## **Limitations**

Do not use product on head gaskets or fuel immersion applications. Allow to fully cure before putting assembly into service. Ensure enough product remains between flanges to be effective in an assembly.

## **Handling and safety**

For maximum shelf life, keep containers sealed when not in use. Keep out of the reach of children. Uncured sealant irritates eyes and skin. Refer to MSDS.

## **Shelf-life**

Sealed containers are guaranteed for 1 year from the ship date when stored in a cool dry area below 70 F.

## **Applicable standards**

Conforms to GM 9985675 and GM low volatility requirements.

## **Limited warranty**

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as warranty, either expressed or applied. User shall rely on his own information and tests to determine suitability of the product for the intended use, and the user assumes all risk and liability resulting from the use of this product. Manufacturer's sole responsibility shall be to replace that portion of product of the manufacturer proves to be defective. Manufacturer shall not be liable to the buyer or any third party for injury, loss or damage directly or indirectly resulting from the use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding by the manufacturer.

This product has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses which implantation within the human body is intended.

**\*\* Customized versions available upon request \*\***